



## Technical Specification Sheet

### NOIR

**Description:**

Iridescent reflective surface wallcovering in Black.

**Construction:**

Polyester/ vinyl face with non-woven backing.

**Application:**

Standard commercial wallcoverings pastes, primers and techniques. For indoor use in environmentally controlled spaces.

**Weight:**

Product Weight (total): 20 oz. per lineal yd.

Poly/Vinyl Weight: 17 oz. per lineal yd.

Fabric Weight: 2.7 oz. per lineal yd. Adhesive:

0.3 oz. per lineal yd. Thickness:

.015 - .030 inches

**Type II Properties:** Breaking Strength, lbs force

Machine direction-warp: Exceeds Type II minimum of 50lbs. Cross Machine

Direction-fill: Exceeds Type II minimum of 55lbs. Tearing Strength, Scale

Machine direction-warp: Exceeds Type II minimum of 25lbs. Cross Machine

Direction-fill: Exceeds Type II minimum of 25lbs. Cold Crack Resistance @

20°F: No Change

Heat Aging (7 days at 158°F): Does not become stiff, brittle, discolored or show loss of grain.

**Specifications:**

Federal Specification: CCC-408-D Type II WA

Specification: W-101 Type II

**Fire Test Ratings:**

ASTM-E84 Tunnel Test: Class A NFPA Life

Safety Code 101: Class A NFPA 286 Corner

Burn Test: Class A

BS476 Parts 6 & 7: Passed all requirements.

CAN/ULC-S 102.2: Passed all requirements.

EU Class Flame (EN15102) : Passed Class B, S2

**Mold/Mildew:**

ASTM-G21 Specifications: Passed all requirements.

**Environmental:**

Made with low VOC vinyl

Tested per CA-1350 Air Quality Standards

Cadmium and Lead Free Formulation

---